

# Impianti post-mix Brave ed Eclipse - Energy Saving

## Brave and Eclipse post-mix coolers - Energy Saving

### Caratteristiche principali

- La serie Brave ed Eclipse ha ottenuto la Certificazione Ambientale in conformità alla norma ISO 14021
- Isolamento della vasca aumentato in modo da ridurre le dispersioni termiche
  - Isolamento della vasca realizzato con poliuretano espanso con gas espandente CO<sub>2</sub> (HFC free)
  - Pannello comandi con scatola di protezione interna, che assicura una maggiore protezione dei componenti elettrici
  - Carrozzeria acciaio inox
  - Centralina elettronica Energy Saving
  - Scarico vasca
  - Predisposto per telemetria
  - Componenti Energy Saving

### Main features

- The Brave and Eclipse range has been awarded Environmental Certification in compliance with ISO 14021
- Increased tank insulation to reduce heat dispersion
  - Tank insulation made from HFC-free CO<sub>2</sub> polyurethane foam
  - Command panel, with internal box to protect electrical parts
  - Stainless steel casing
  - Energy-Saving electronic control unit
  - Tank drainage system
  - Telemetry predisposition
  - Energy-Saving components



|  |              | BRAVE 60 ES      | BRAVE 90 ES    | BRAVE 120 ES    |
|--|--------------|------------------|----------------|-----------------|
| COMPRESSORE - COMPRESSOR   | HP           | 5/8              | 1              | 2 x 1           |
| CAPACITÀ COMPRESSORE<br>COOLING CAPACITY   | WATT         | 1050             | 2100           | 2 x 2100        |
| POTENZA ASSORBITA - INPUT POWER  | W            | 1000             | 1200           | 2000            |
| CAPACITÀ VASCA - TANK CAPACITY   | LT           | 56               | 82             | 100             |
| BANCO GHIACCIO - ICE BANK  | KG           | 20               | 34             | 50              |
| TEMPERATURA DI USCITA BEVANDA<br>BEVERAGE OUTLET TEMPERATURE   |              | < 4,4 °C         | < 4,4 °C       | < 4,4 °C        |
| POMPA CARBONAZIONE<br>CARBONATION PUMP   | LT/H         | 400              | 400            | 2 x 400         |
| VOLT - HERTZ *   | V/H          | 230/50           | 230/50         | 230/50          |
| POMPA DI RICIRCOLO SODA<br>SODA RECIRCULATION PUMP   | LT/H         | 300              | 300            | 2 x 300         |
| VOLUME CARBONATORE<br>CARBONATOR VOLUME  | TOT CC       | 2262             | 3500           | 6200            |
| LITRI EROGABILI FINO ESAURIMENTO<br>BANCO GHIACCIO A DIVERSE<br>TEMPERATURE BEVANDA                            | 16°C<br>24°C | 133<br>80        | 260<br>156     | 350<br>200      |
| LITERS THAT CAN BE CHILLED TILL<br>COMPLETE DEPLETION OF ICE BANK,<br>AT DIFFERENT TEMPERATURES OF BEER IN KEG | 32°C<br>43°C | 57<br>41         | 111<br>80      | 145<br>105      |
| REFRIGERANTE - REFRIGERANT   |              | R290             | R290           | R290            |
| MAX N. DI BOBINE SCIROPPI<br>MAX NO. OF SYRUPS COILS N°  |              | 8                | 10             | 12              |
| DIMENSIONI - DIMENSIONS  | CM           | 72,2x49,1x H60,7 | 92x57,6x H81,6 | 117x68,1x H87,1 |
| PESO - WEIGHT  | KG           | 95               | 130            | 235             |

\* Su richiesta disponibile tensione a 115V - 115V power available upon request

#### Impianto post-mix sottobanco Brave 60 Energy Saving:

- Carrozzeria in acciaio inox 430
- Pompa interna acqua piatta
- Motoventilatore, agitatore, motore di ricircolo soda Energy Saving
- 8 sciroppi e 1 birra massimo

#### Impianto post-mix sottobanco Brave 90 Energy Saving:

- Carrozzeria con ruote in acciaio inox 430
- Pompa interna acqua piatta (su richiesta)
- Motoventilatore, agitatore, motore di ricircolo soda Energy Saving
- 8 sciroppi e 2 birre massimo

#### Impianto post-mix sottobanco Brave 120 Energy Saving:

- Carrozzeria con ruote in acciaio inox 430
- Pompa interna acqua piatta comandata da pressostato o ritorno elettrico valvole erogazione
- Motoventilatore, agitatore, motore di ricircolo: soda Energy Saving
- 8 sciroppi

#### Impianto post-mix sottobanco Eclipse Energy Saving:

- Pannelli in acciaio inox
- Serpentine in Aisi 304
- Ricircolo soda
- Valvola acqua piatta con centralina Energy Saving
- 6 sciroppi e 2 birre

#### Brave 60 Energy-Saving post-mix undercounter cooler:

- 430 stainless steel casing
- Internal pump for still water
- Energy-Saving fan unit, agitator, soda recirculation motor
- Up to 8 syrups and 1 beer

#### Brave 90 Energy-Saving post-mix undercounter cooler:

- 430 stainless steel casing with wheels
- Internal kit for still water (on request)
- Energy-Saving fan unit, agitator, soda recirculation motor
- Up to 8 syrups and 2 beers

#### Brave 120 Energy-Saving post-mix undercounter cooler:

- 430 stainless steel casing with wheels
- Internal kit for still water led by pressure switch or dispensing valves electrical return
- Energy-Saving fan unit, agitator, soda recirculation motor
- Up to 8 syrups

#### Eclipse Energy-Saving post-mix undercounter cooler:

- Stainless steel panels
- Aisi 304 coils
- Soda recirculation
- Still water valve with Energy Saving control unit
- Up to 6 syrups and 2 beers



ECLIPSE H ES



ECLIPSE V ES



BRAVE 120 ES



BRAVE 60 ES



BRAVE 90 ES