

# Impianti post-mix Brave ed Eclipse - Energy Saving

## Brave and Eclipse post-mix coolers - Energy Saving

### Caratteristiche principali

- La serie Brave ed Eclipse ha ottenuto la Certificazione Ambientale in conformità alla norma ISO 14021
- Isolamento della vasca aumentato in modo da ridurre le dispersioni termiche
  - Isolamento della vasca realizzato con poliuretano espanso con gas espandente CO<sub>2</sub> (HFC free)
  - Pannello comandi con scatola di protezione interna, che assicura una maggiore protezione dei componenti elettrici
  - Carrozzeria acciaio inox
  - Centralina elettronica Energy Saving
  - Scarico vasca
  - Predisposto per telemetria
  - Componenti Energy Saving

### Main features

- The Brave and Eclipse range has been awarded Environmental Certification in compliance with ISO 14021
- Increased tank insulation to reduce heat dispersion
  - Tank insulation made from HFC-free CO<sub>2</sub> polyurethane foam
  - Command panel, with internal box to protect electrical parts
  - Stainless steel casing
  - Energy-Saving electronic control unit
  - Tank drainage system
  - Telemetry predisposition
  - Energy-Saving components



		BRAVE 60 ES	BRAVE 90 ES	BRAVE 120 ES
COMPRESSORE - COMPRESSOR	HP	5/8	1	2 x 1
CAPACITÀ COMPRESSORE COOLING CAPACITY	WATT	1050	2100	2 x 2100
POTENZA ASSORBITA - INPUT POWER	W	1000	1200	2000
CAPACITÀ VASCA - TANK CAPACITY	LT	56	82	100
BANCO GHIACCIO - ICE BANK	KG	20	34	50
TEMPERATURA DI USCITA BEVANDA BEVERAGE OUTLET TEMPERATURE		< 4,4 °C	< 4,4 °C	< 4,4 °C
POMPA CARBONAZIONE CARBONATION PUMP	LT/H	400	400	2 x 400
VOLT - HERTZ *	V/H	230/50	230/50	230/50
POMPA DI RICIRCOLO SODA SODA RECIRCULATION PUMP	LT/H	300	300	2 x 300
VOLUME CARBONATORE CARBONATOR VOLUME	TOT CC	2262	3500	6200
LITRI EROGABILI FINO ESAURIMENTO BANCO GHIACCIO A DIVERSE TEMPERATURE BEVANDA	16°C 24°C	133 80	260 156	350 200
LITERS THAT CAN BE CHILLED TILL COMPLETE DEPLETION OF ICE BANK, AT DIFFERENT TEMPERATURES OF BEER IN KEG	32°C 43°C	57 41	111 80	145 105
REFRIGERANTE - REFRIGERANT		R290	R290	R290
MAX N. DI BOBINE SCIROPPI MAX NO. OF SYRUPS COILS N°		8	10	12
DIMENSIONI - DIMENSIONS	CM	72,2x49,1x H60,7	92x57,6x H81,6	117x68,1x H87,1
PESO - WEIGHT	KG	95	130	235

\* Su richiesta disponibile tensione a 115V - 115V power available upon request

#### Impianto post-mix sottobanco Brave 60 Energy Saving:

- Carrozzeria in acciaio inox 430
- Pompa interna acqua piatta
- Motoventilatore, agitatore, motore di ricircolo soda Energy Saving
- 8 sciroppi e 1 birra massimo

#### Impianto post-mix sottobanco Brave 90 Energy Saving:

- Carrozzeria con ruote in acciaio inox 430
- Pompa interna acqua piatta (su richiesta)
- Motoventilatore, agitatore, motore di ricircolo soda Energy Saving
- 8 sciroppi e 2 birre massimo

#### Impianto post-mix sottobanco Brave 120 Energy Saving:

- Carrozzeria con ruote in acciaio inox 430
- Pompa interna acqua piatta comandata da pressostato o ritorno elettrico valvole erogazione
- Motoventilatore, agitatore, motore di ricircolo: soda Energy Saving
- 8 sciroppi

#### Impianto post-mix sottobanco Eclipse Energy Saving:

- Pannelli in acciaio inox
- Serpentine in Aisi 304
- Ricircolo soda
- Valvola acqua piatta con centralina Energy Saving
- 6 sciroppi e 2 birre

#### Brave 60 Energy-Saving post-mix undercounter cooler:

- 430 stainless steel casing
- Internal pump for still water
- Energy-Saving fan unit, agitator, soda recirculation motor
- Up to 8 syrups and 1 beer

#### Brave 90 Energy-Saving post-mix undercounter cooler:

- 430 stainless steel casing with wheels
- Internal kit for still water (on request)
- Energy-Saving fan unit, agitator, soda recirculation motor
- Up to 8 syrups and 2 beers

#### Brave 120 Energy-Saving post-mix undercounter cooler:

- 430 stainless steel casing with wheels
- Internal kit for still water led by pressure switch or dispensing valves electrical return
- Energy-Saving fan unit, agitator, soda recirculation motor
- Up to 8 syrups

#### Eclipse Energy-Saving post-mix undercounter cooler:

- Stainless steel panels
- Aisi 304 coils
- Soda recirculation
- Still water valve with Energy Saving control unit
- Up to 6 syrups and 2 beers



ECLIPSE H ES



ECLIPSE V ES



BRAVE 120 ES



BRAVE 60 ES



BRAVE 90 ES