

Soprabanchi post-mix Polo, Smart e Juice

Polo, Smart and Juice post-mix overcounters

Caratteristiche tecniche

- Pannello frontale con logo illuminato
- Ampia capacità del banco ghiaccio
- Massima efficienza
- Miglior rapporto qualità-prezzo
- Logo retroilluminato

Polo 30 e 50 sono disponibili su richiesta:

- con un massimo di 7 serpentine in acciaio inox (pianta singola)
- con pompa 7m, 12m, 18m
- con pompa Compact 6.5 m con agitatore EBM
- con termostato estate/inverno

Smart è disponibile su richiesta:

- con un massimo di 7 serpentine in acciaio inox (pianta singola)
- con pompa 7m, 12m, 18m
- con pompa Compact 6.5 m con agitatore EBM
- con termostato estate/inverno

Technical features

- Front panel with illuminated branding
- Large ice-bank capacity
- Maximum efficiency
- Best value for money
- Backlit logo

Polo 30 and 50 cooler are available upon request:

- with up to 7 st. steel coils (single plant)
- with 7m, 12m, 18m pump
- with Compact pump 6.5 m with EBM agitator
- with summer/winter thermostast

Smart cooler are available upon request:

- with up to 7 st. steel coils (single plant)
- with 7m, 12m, 18m pump
- with Compact pump 6.5 m with EBM agitator
- with summer/winter thermostast

		POLO 30/L	POLO 50/L	SMART
COMPRESSORE - COMPRESSOR	HP	1/3	1/2	1/6
CAPACITÀ REFRIGERANTE - COOLING POWER	WATT	571	905	
CAPACITÀ VASCA - TANK CAPACITY	LT	25	45	
BANCO GHIACCIO - ICE BANK	KG	12	22	
CARROZZERIA - CASING		ACCIAIO INOX ST. STEEL	ACCIAIO INOX ST. STEEL	
POMPA CARBONAZIONE - CARBONATION PUMP	LT/H	400	400	
VOLUME CARBONATORE - CARBONATOR VOLUME	TOT CC	1710	2000	
NUMERO DI VALVOLE - NO. OF VALVES	N°	4-5	5-6	
DIMENSIONI - DIMENSIONS	CM	38,8x77xH70,3	44,5x85,4xH70,8	
PESO - WEIGHT	KG	59	68	



		POLO JUICE 30	SMART JUICE
COMPRESSORE - COMPRESSOR	HP	1/3	1/6
REFRIGERANTE - REFRIGERANT		R134A OR R290 R134A O R290	R134A OR R290 R134A O R290
CAPACITÀ SERBATOIO ACQUA - WATER TANK CAPACITY	LT	25	12
BANCO GHIACCIO - ICE BANK	KG	12	4,5
TEMPERATURA SCIROPPO IN INGRESSO SYRUP INLET TEMPERATURE		LITRI EROGABILI FINO AD ESAURIMENTO BANCO LITRES THAT CAN BE DISPENSED BEFORE COMPLETE ICE BANK DEPLETION	
	T° 20	96	24
	T° 24	69	17
	T° 32	44	11
	T° 40	32	8
CARROZZERIA/HOUSING		AISI/430	AISI/430
TENSIONE/POWER	V/HZ	230 - 50/60	230 - 50/60
MATERIALE SERPENTINE/COIL MATERIAL		AISI/430 D.P.	AISI/430 D.P.
POMPA ACQUA/WATER PUMP	L/H	360	360
POMPA SUCCO/JUICE PUMP	W	11,5	11,5
POLPA DI FRUTTA/JUICE PULP	L/H	38	38
PESO COMPLESSIVO/SHIPPING WEIGHT	KG	59	39
PRESTAZIONE DI USCITA (TEMPERATURA AMBIENTE 32°C) OUTPUT PERFORMANCE (ROOM TEMPERATUR 32°C)	W	571	250



POLO 30/L



SMART



POLO JUICE



SMART JUICE